

Multi-use linear LED light.

Your partner for next-generation lighting

Tri Proof

Protection class : IP65
Beam diffusion angle: 120°
Colour temperature : 3000K – 7000K
Colour rendering index : >80Ra
Power supply : 230v, 50~60 Hz
Cos Φ : > 0.95



Four power rates available :

Model	Luminous flux	Dimensions	Net weight
T-P-20W	1900lm	600x86x72mm	1.4Kg
T-P-40W	3900lm	900x86x72mm	2.0Kg
T-P-60W	5900lm	1200x86x72mm	3.0Kg
T-P-80W	7900lm	1500x86x72mm	3.4Kg

High quality LED projectors, integrating components from reputable suppliers (LED - SMD 2835, CE Approved Power Supply). Thanks to the distribution of LEDs over a large area, the glare often associated with LEDs is limited and good heat dissipation is ensured. The extruded aluminium casing and the polycarbonate lens are sturdy and have a very long service life (50,000 hours).

This lamp is guaranteed for five years. Designed for office, sports or industrial lighting applications, thanks to its elegance and even distribution of light, it is also certified to comply with the latest European lighting standards.

Tri Proof-LHB11

Protection class :	IP65 & IK08
Beam diffusion angle:	120°.
Colour temperature :	3000K – 6000K
Colour rendering index :	>80Ra
Power supply :	230v, 50~60 Hz
Cos Φ :	> 0.90



Three power rates available :

Model	Luminous flux	Dimensions	Net weight
T-P-LHB11-40W	5800lm	647x97x89mm	1.4Kg
T-P-LHB11-60W	9000lm	1247x97x89mm	2.3KG
T-P-LHB11-80W	12000lm	1547x97x89mm	2.8KG

High quality LED projectors, integrating components from reputable suppliers (LED - SMD 2835, CE Approved Power Supply). Thanks to the distribution of LEDs over a large area, the glare often associated with LEDs is limited and good heat dissipation is ensured. The extruded aluminium casing and the polycarbonate lens are sturdy and have a very long service life (50,000 hours).

Connection option connectable in a line (max - 10)

Options: -1-10V / DALI / Zigbee Variable and microwave motion detector

This lamp is guaranteed for five years. Designed for office, sports or industrial lighting applications, thanks to its elegance and even distribution of light, it is also certified to comply with the latest European lighting standards.

