

FL35

Protection class :	IP66, IK08
Beam diffusion angle:	Asymmetric
Colour temperature :	4000K – 5700K
Colour rendering index :	Ra70/Ra80
Power supply :	110~277 50~60Hz
	Option 277-480Vac
Cos Φ :	> 0.90



Three power rates available


Model	Luminous flux	Dimensions	Net weight
FL35-200W	26000 lm	327×356×199mm	6 kg
FL35-400W	52000 lm	511×356×336mm	11 kg
FL35-600W	78000 lm	576×356×414mm	16 kg

High quality LED projectors, integrating components from reputable suppliers (Seoul 5050 LED, Sosen power supply). Thanks to the distribution of LEDs over a large area, the glare often associated with LEDs is limited and good heat dissipation is ensured. The anodized aluminium casing and the polycarbonate lens are sturdy and provide a very long service life (Driver >50,000Hrs (@Ta=25°C), LED >110000hrs-L80 (@Ta=25°C)).

Available in variable option: 0-10v, DALI, DMX & Zigbee.

This lamp is designed for Jofam to meet the latest requirements for sports lighting in Switzerland in terms of ULR, GR and LI. It is also certified according to the latest European lighting standards and guaranteed for five years.

FL35-200W - EPA 0.06



FL35-600W – EPA 0.14

