

Your partner for next-generation lighting

SP07

Protection class : IP23, IK10
 Beam diffusion angle : 30°,60°,90° & Asymmetric
 Colour temperature : 4000K – (3000-5000K)
 Colour rendering index : >80Ra
 Power supply: 110~277 50~60 Hz
 Cos Φ: > 0.93
 Product colour: White (RAL9016)



Three power rates available:

| Model | Luminous flux | Dimensions | Net weight |
|-----------|---------------|---------------|------------|
| SP07-120W | 20400 lm | 1320x238x76mm | 8.4 kg |
| SP07-160W | 26560 lm | 1320x238x76mm | 8.4 kg |
| SP07-200W | 32400 lm | 1320x238x76mm | 8.6 kg |

High quality LED projectors, integrating components from reputable suppliers (SMD LED, Sosen power supply). Thanks to the distribution of LEDs over a large area, the glare often associated with LEDs is limited and good heat dissipation is ensured. The anodized aluminium casing and the polycarbonate lens are sturdy and have a very long service life 107,000hrs (L80@Ta=25°C).

Available as option: - 0-10v, DALI & ZigBee variable plus an extensive range of control and mounting accessories.

This lamp is guaranteed for five years, for sports lighting applications, it is also certified to the latest European lighting standards.

