

Your partner for next-generation lighting

## Series - K

Protection class : IP66, IK8  
 Beam diffusion angle: IES type I - III.  
 Colour temperature : 4000K – 5700K  
 Colour rendering index : >70Ra  
 Alimentation : 110~277 50~60 Hz  
 Cos  $\Phi$  : > 0.90



### Nine power rates available

Model	Luminous flux	Dimensions	Net weight
Séries-K-25W	2875 lm	614 x 224 x 135	5.8 kg
Séries-K-35W	4025 lm	614 x 224 x 135	6.0 kg
Séries-K-55W	6325 lm	614 x 224 x 135	6.2 kg
Séries-K-60W	7500 lm	726 x 357 x 127	7.8 kg
Séries-K-90W	11250 lm	726 x 357 x 127	8.1 kg
Séries-K-120W	15000 lm	726 x 357 x 127	8.2 kg
Séries-K-150W	18750 lm	861 x 447 x 153	12.0 kg
Séries-K-180W	22500 lm	861 x 447 x 153	12.1 kg
Séries-K-200W	25000 lm	861 x 447 x 153	12.2 kg

High quality LED projectors, integrating components from reputable suppliers (Phillips LED, Meanwell power supply). Thanks to the distribution of LEDs over a large area, the glare often associated with LEDs is limited and good heat dissipation is ensured. The anodized aluminium casing and the polycarbonate lens are sturdy and have a very long service life (75,000 hours).

Optional variable: 1-10V DC or PWM Signal or motion detector, or photocell.

This lamp is guaranteed for five years, for heavy duty lighting applications, it is also certified to the latest European lighting standards.

