

Your partner for next-generation lighting

ST36

Protection class: IP66, IK09, 10KV
 IEC protection: Class I, option II
 Beam diffusion angle: IES type I - III.
 Colour temperature: 3000K – 5000K
 Colour rendering index: >70Ra, option >80Ra.
 Power: 110~277 50~60 Hz
 Cos Φ: > 0.95
 Body: Silver (RAL9006)



Ten power rates available

Model	Luminous flux	L1 xW1 xH1	Net weight
ST36-20W	3200 lm	558*220*199mm	4.7kg
ST36-30W	4800 lm	558*220*199mm	4.7kg
ST36-40W	6400 lm	558*220*199mm	4.7kg
ST36-60W	9600 lm	658*220*201mm	5.8kg
ST36-75W	12000 lm	658*220*201mm	5.8kg
ST36-100W	16000 lm	658*220*201mm	5.8kg
ST36-120W	19200 lm	713*270*202mm	8.1kg
ST36-150W	24000 lm	713*270*202mm	8.1kg
ST36-180W	28800 lm	783*285*204mm	8.3kg
ST36-200W	32000 lm	783*285*204mm	8.3kg

High quality LED projectors, integrating components from reputable suppliers (Luminled LED, Tridonic power supply). Thanks to the distribution of LEDs over a large area, the glare often associated with LEDs is limited and good heat dissipation is ensured. The anodized aluminium casing and the polycarbonate lens are sturdy and have a very long service life (100,000 hours).

Optional variable: 1-10V DC, DALI or motion detector, or photocell.

This lamp is guaranteed for five years, for heavy duty lighting applications, it is also certified to the latest European lighting standards.

